



INSTRUCTIONS FOR ASSEMBLY OF LORO



Unwrap and remove all parts from each box. Keep the boxes and packing material until the cage is assembled. In case of return or exchange failure to return product in similar condition as received could result in limited reimbursement. Check to ensure you have all the following parts:

- ROOF TOP (2 PIECES)
- ROOF FRONT
- ROOF BACK
- TOP GRATE
- 1 FRONT PANEL (WITH DOOR)
- 1 BACK PANEL
- 2 SIDE PANELS (ONE WITH CUP HOLDER DOORS)
- PERCH
- 4 LEGS
- 2 CUP HOLDERS AND CUPS
- BOTTOM GRATE
- TRAY
- MAIN BASE
- 4 CASTERS
- BOTTLE OF TOUCH UP PAINT

Cage Assembly (see attached numbered diagram):

1. Insert CASTERS into each LEG (they can be installed using a rubber mallet).
2. Set the MAIN BASE on top of the LEGS (on each leg there is a small open sleeve that must face each other on the short side of the base).
3. Insert FRONT PANEL onto the main base.
4. Insert BACK PANEL onto the main base.
5. Slide SIDE PANEL lower tabs into the small open sleeves on the LEGS, at the bottom of the FRONT and BACK PANELS, then push the upper tabs into sleeves at the top.
6. Insert pegs on the TOP GRATE into corresponding holes on the top of the PANELS to hold all PANELS together.
7. Insert ROOF FRONT and ROOF BACK (has hole for electrical cord) into TOP GRATE.
8. Place larger ROOF TOP panel (one with angled peak) onto ROOF FRONT and BACK. Slide up a small amount until it settles into place.
9. Insert the top edge of the second ROOF TOP panel into the first panel and onto ROOF FRONT and BACK. Slide up a small amount until it settles into place.
10. If desired, slide BOTTOM GRATE into the track just below the front door.
11. Slide the TRAY into the track below the grate. If you do not want to use the grate, you may slide the bottom tray into the track just below the front door.
12. Install the PERCH on the inside of the cage. The notches fit over the cage bars on each side.
13. With the feed doors open, insert the CUP HOLDERS into the tubes on the inside of the doors.
14. Insert a CUP into each of the CUP HOLDERS.
15. To install each LATCH, first remove the knob by unthreading it. Ensure the spring is placed over the round end of latch. Insert the assembly into the lock sleeve mounted onto the cage door so that the round end protrudes through the opposite end. Position the assembly so that the threaded hole is visible through the front of the latch and screw the knob through the lock sleeve into the threaded hole on the latch. Turn counter-clockwise to loosen and open the door. When securing the door, tighten in the opposite direction to go in to the "lock" position.

